Hangler 2-aks 3-vejs 11,8T Tipkærre, Tipper



Poulsen Trucks & Trailers ApS Haarup Skovvej 7, Haarup 8600 Silkeborg

Sælger Philip K. Bredahl philip@poulsentrucks.com

- +45 74 67 11 12
- +45 28 90 01 31

and the first the state of the control of the state of th				
Basis				
Type	Drawbar			
Aksel	2			
Stand	Ny			
Registration				
Year	2025			
Ref. no.	7119			
Brakes				
Drum brakes	~			
Incoupling				
Electrical coupier	2x7-polet			
Air- coupier	DuoMatic			

0	です。「なってくらる」の語	1000	
	Chassis		
	Total axle load		10.900kg
	Axle type		BPW
	Airsuspension		~
	Kingpin pressure		900kg
	Total length		7.000mm
	Drawbar height	750-	1.050mm
	Tyres		
	Dimensions	235/7	75 R17,5"
	1st axle tyres L-F	R%	100-100
	2nd axle tyres L-	R%	100-100

Weight	
Loading capacity	8.640kg
Total weight	11.800kg
Empty weight	3.160kg
truck body / box	
Bottom	Stål
Side board	✓
Front board	<b>✓</b>
Height of side board	450mm
Tie-down rings in botton	n 🗸
5 ton lashing eyes	10 stk.
Length inside	5.000mm
Inside width	2.420mm

## Beskrivelse

FABRIKSNY SMALL AND SMART 11, 8T HANGLER 3-WAY TIPCART!

3-Way Tip via 1-string hydraulic from the tractor. (Backtip + page tips for both sides)

The cart is equipped with BPW axles with drum brakes on parabolic springs.

The base is constructed of steel, with removable steel sides + steel tailgate. The front is bolt mounted and can also be removed if desired.

The sides are equipped with spring-features as seen on the front, which makes it simple for a person to open and close the sides without difficulty.

- 2 pcs loose 8,000 kg (pair) 3,000 x 360mm alu ramps stored in the tray between the chassis rails-are pulled out at the back of the cart.
- 1,750 mm long drawbar with 57mm wooden bunk. The drawbar is height adjustable. Galvanized chassis.

For further information call or write to us:

+ 45 7467 1112/philip@poulsenbiler.com



















